

Watermist

The Marine Range Watermist fire extinguisher is available in 3 and 6 litre models, and approved to Marine Equipment Directive 2014/90/EU. Both models come complete with colour coding and are Kitemark certified to BS EN3, UKCA and CE marked. For use on Class A fires (solid materials) and Class F fires (cooking oil and fats). They have also been fire tested* on Class B fires (flammable liquids or liquefiable solids). Electrical risk (class E) covered up to 1000v.

- › Quality deep drawn cylinders.
- › High quality heavy-duty brass valves.
- › Colour coded headers, handles and bases.
- › Spray nozzle complies with the dielectric test of BS EN3-7, clause 9.



MADE IN THE UK



COLOUR CODED



FULLY CERTIFIED



GUARANTEE



› EWMS3MED : 3 Litre Watermist

› EWMS6MED : 6 Litre Watermist

Product Certification and Specification



0832



bsi.
Portable Fire
Extinguishers
KITEMARK™

KM 57904
BS EN 3

UK
CA
0086

CE
2797



* Please note whilst Jactone Watermist Extinguishers have been Class B fire tested it is not possible to certify this performance under BS EN3 as the fire sizes are outside of EN3 limits. Our fire testing and video evidence confirms safe and very creditable performance for situations where Class B is not the primary risk.

› EXTINGUISHER :	
› PRODUCT CODE :	
› MEDIUM :	
› PROPELLANT :	
› FIRE RATING :	
› OPERATING TEMPERATURE :	
› OPERATING PRESSURE :	
› AVERAGE DISCHARGE TIME :	
› HEIGHT & DIAMETER :	
› FILLED WEIGHT & EMPTY WEIGHT :	
› PACKING SPEC (HxWxD) :	

3 Litre Watermist
EWMS3MED
Water
Nitrogen gas
8A 21B* 25F
+5°C to +60°C
15 bar at 20°C
15.26 seconds
Height 435mm Diameter 160mm
Filled 6.1kg Empty 3.1kg
450 x 177 x 177mm

6 Litre Watermist
EWMS6MED
Water
Nitrogen gas
13A 34B* 40F
+5°C to +60°C
15 bar at 20°C
26.73 seconds
Height 552mm Diameter 189mm
Filled 11kg Empty 4.9kg
549 x 205 x 205mm