

Foam

The Basic Range Foam fire extinguisher is available in 2, 6 and 9 litre models. These foam extinguishers are designed for use on Class A fires (solid materials) and Class B fires (flammable liquids or liquefiable solids). All models are Kitemark certified to BS EN3 and CE marked.

- › Deep drawn cylinders*
- › Colour coded header labels.
- › Nickel plated brass valves.



FULLY CERTIFIED

*6 litre and 9 litre models only.



› EFS2Z : 2 Litre Foam



› EFS6Z : 6 Litre Foam



› EFS9Z : 9 Litre Foam

Product Certification and Specification



KM 57904
BS EN 3



0036

	2 Litre Foam	6 Litre Foam	9 Litre Foam
› EXTINGUISHER :	EFS2Z	EFS6Z	EFS9Z
› PRODUCT CODE :	Aqueous Film Forming Foam	Aqueous Film Forming Foam	Aqueous Film Forming Foam
› MEDIUM :	Nitrogen gas	Nitrogen gas	Nitrogen gas
› PROPELLANT :	5A 34B	13A 144B	21A 183B
› FIRE RATING :	0°C to +60°C	0°C to +60°C	0°C to +60°C
› OPERATING TEMPERATURE :	12 bar at 20°C	12 bar at 20°C	12 bar at 20°C
› OPERATING PRESSURE :	19 seconds	15 seconds	15 seconds
› AVERAGE DISCHARGE TIME :	H 378mm D 110mm	H 450mm D 162mm	H 525mm D 184mm
› HEIGHT & DIAMETER :	3.65kg	10.30kg	14.50kg
› FILLED WEIGHT :	405 x 135 x 115mm	570 x 175 x 170mm	640 x 205 x 200mm
› PACKING SPEC (HxWxD) :			