

Powder

The Basic Range Powder fire extinguisher is available in 1, 2, 6 and 9kg ABC powder models. For use on Class A, B and C fires making them suitable for use in environments containing multiple fire risks. They are highly effective against petrol and volatile liquids which makes them ideal for vehicle protection. All models are Kitemark certified to BS EN3 and CE marked.

- › Deep drawn cylinders*
- › Colour coded header labels.
- › Nickel plated brass valves.



FULLY CERTIFIED

*6kg and 9kg models only.



Product Certification and Specification



- › EXTINGUISHER :
- › PRODUCT CODE :
- › MEDIUM :
- › PROPELLANT :
- › FIRE RATING :
- › OPERATING TEMPERATURE :
- › OPERATING PRESSURE :
- › AVERAGE DISCHARGE TIME :
- › HEIGHT & DIAMETER :
- › FILLED WEIGHT :
- › PACKING SPEC (HxWxD) :

1kg ABC Powder	2kg ABC Powder	6kg ABC Powder	9kg ABC Powder
EPS1Z	EPS2Z	EPS6Z	EPS9Z
ABC Powder	ABC Powder	ABC Powder	ABC Powder
Nitrogen gas	Nitrogen gas	Nitrogen gas	Nitrogen gas
5A 34B C	13A 70B C	27A 144B C	34A 233B C
-30°C to +60°C	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C
14 bar at 20°C	14 bar at 20°C	14 bar at 20°C	14 bar at 20°C
6 seconds	9 seconds	15 seconds	15 seconds
H 330mm D 85mm	H 378mm D 110mm	H 450mm D 150mm	H 495mm D 184mm
1.96kg	3.47kg	9.40kg	13.70kg
360 x 135 x 90mm	405 x 135 x 115mm	570 x 170 x 165mm	605 x 205 x 200mm