

EcoFoam

The Marine Range EcoFoam fire extinguisher is available in 6 and 9 litre models, and approved to Merchant Shipping (Marine Equipment) Regulations SI 2016/1025. The EcoFoam is for use on Class A fires (solid materials) and Class B fires (flammable liquids or liquefiable solids). Both models come complete with colour coded handle, header label and base and are Kitemark certified to BS EN3, UKCA and CE marked.

- › Bio based high performance extinguishant.
- › Quality deep drawn cylinders.
- › High quality heavy-duty brass valves.
- › Colour coded headers, handles and bases.
- › Spray nozzle complies with the dielectric test of BS EN3-7, clause 9.



MADE IN THE UK



COLOUR CODED



FULLY CERTIFIED



GUARANTEE



› EFS6ECOMED : 6 Litre EcoFoam

› EFS9ECOMED : 9 Litre EcoFoam

Product Certification and Specification



0832



KM 57904
BS EN 3



0086



2797



› EXTINGUISHER :	
› PRODUCT CODE :	
› MEDIUM :	
› PROPELLANT :	
› FIRE RATING :	
› WATER & ECOFOAM CONTENT :	
› OPERATING TEMPERATURE :	
› OPERATING PRESSURE :	
› AVERAGE DISCHARGE TIME :	
› HEIGHT & DIAMETER :	
› FILLED WEIGHT & EMPTY WEIGHT :	
› PACKING SPEC (HxWxD) :	

6 Litre EcoFoam	9 Litre EcoFoam
EFS6ECOMED	EFS9ECOMED
EcoFoam	EcoFoam
Nitrogen gas	Nitrogen gas
21A 144B	27A 183B
5.91 Litres Water 0.09 Litres EcoFoam	8.865 Litres Water 0.135 Litres EcoFoam
+5°C to +60°C	+5°C to +60°C
15 bar at 20°C	15 bar at 20°C
56 seconds	79.65 seconds
Height 517mm Diameter 160mm	Height 552mm Diameter 189mm
Filled 9.9kg Empty 3.85kg	Filled 14kg Empty 4.9kg
529 x 177 x 177mm	549 x 205 x 205mm