

Fire Extinguishers



Powder A B F 4

The Marine Range Powder fire extinguisher is available in 2kg, 4kg, 6kg and 9kg ABC powder models, approved to Merchant Shipping (Marine Equipment) Regulations SI 2016/1025. For use on Class A, B and C fires making them suitable for use in environments containing multiple fire risks. They are highly effective against petrol and volatile liquids which makes them ideal for vehicle protection. All models come complete with the distinctive Jactone colour coded handle, header label and base* and are Kitemark certified to BS EN3, UKCA and CE marked.

- Quality deep drawn cylinders*.
- > High quality heavy-duty brass valves.
- > Colour coded headers, handles and bases*.









MADE IN THE UK COLOUR CODED FULLY CERTIFIED







EPS9MED: 9kg ABC Powde

*4kg, 6kg and 9kg models only.

Product Certification and Specification











> EXTINGUISHER :

> PRODUCT CODE:

> MEDIUM:

> PROPELLANT:

> FIRE RATING :

) OPERATING TEMPERATURE :

OPERATING PRESSURE:

AVERAGE DISCHARGE TIME :

HEIGHT & DIAMETER:

> FILLED & EMPTY WEIGHTS:

> PACKING SPEC (HxWxD):

EPS2MED ABC 40 Dry Powder Nitrogen gas 13A | 70B | C -20°C to +60°C 15 bar at 20°C 9.5 seconds

2kg ABC Powder

H 391mm | D 108mm F 3.2kg | E 1.2kg 393 x 159 x 117mm

F 6.95kg | E 2.9kg 415 x 175 x 175mm

H 411mm | D 160mm

EPS4MED

Nitrogen gas

21A | 113B | C

-20°C to +60°C

15 bar at 20°C

12.9 seconds

ABC 40 Dry Powder

ABC 40 Dry Powder Nitrogen gas 27A | 183B | C -20°C to +60°C 15 bar at 20°C 16.1 seconds H 517mm | D 160mm F 9.55kg | E 3.5kg 529 x 177 x 177mm

EPS9MED ABC 40 Dry Powder Nitrogen gas 43A | 233B | C -20°C to +60°C 15 bar at 20°C 16.7 seconds H 552mm | D 189mm F 13.6kg | E 4.5kg 549 x 205 x 205mm

Issue 25.0