

Powder

The Basic Range Powder fire extinguisher is available in 1 and 2kg ABC powder models. For use on Class A, B and C fires making them suitable for use in environments containing multiple fire risks. They are highly effective against petrol and volatile liquids which makes them ideal for vehicle protection. All models are Kitemark certified to BS EN3 and CE marked.

- › Colour coded header labels.
- › Nickel plated brass valves.



FULLY CERTIFIED



› EPS1Z : 1kg ABC Powder



› EPS2Z : 2kg ABC Powder

Product Certification and Specification



› EXTINGUISHER :	
› PRODUCT CODE :	
› MEDIUM :	
› PROPELLANT :	
› FIRE RATING :	
› OPERATING TEMPERATURE :	
› OPERATING PRESSURE :	
› AVERAGE DISCHARGE TIME :	
› HEIGHT & DIAMETER :	
› FILLED WEIGHT :	
› PACKING SPEC (HxWxD) :	

1kg ABC Powder	2kg ABC Powder
EPS1Z	EPS2Z
ABC Powder	ABC Powder
Nitrogen gas	Nitrogen gas
5A 34B C	13A 70B C
-30°C to +60°C	-30°C to +60°C
14 bar at 20°C	14 bar at 20°C
6 seconds	9 seconds
H 330mm D 85mm	H 378mm D 110mm
1.96kg	3.47kg
360 x 135 x 90mm	405 x 135 x 115mm