

ABC Powder



The 600g ABC Powder aerosol extinguisher is Kitemark certified to BS 6165. The stored pressure ABC powder aerosol extinguisher is suitable for use on Class A, B and C fires meaning that it's ideally suited for domestic and leisure use. Also highly effective against petrol and volatile liquids, which make them ideal for vehicle protection.

- › Aluminium lightweight body.
- › Controlled discharge.
- › Available in red or silver body.
- › Mounting bracket included.
- › No formal maintenance required.
- › Not suitable for use on deep fat fryer fires.



MADE IN THE UK



FULLY CERTIFIED



GUARANTEE



Mounting bracket included

› AEABC600R : 600g ABC Powder



› AEABC600S : 600g ABC Powder



BOATS & MARINE



DOMESTIC



AUTOMOBILES



CARAVANS

Product Certification and Specification



UK
CA



› EXTINGUISHER :	600g ABC Powder
› PRODUCT CODE :	AEABC600R
› MEDIUM :	ABC 40 Powder
› PROPELLANT :	Nitrogen gas
› FIRE RATING :	3A 21B C
› OPERATING TEMPERATURE :	-20°C to +50°C
› AVERAGE DISCHARGE TIME :	6 seconds
› RANGE OF DISCHARGE :	2-3 metres
› HEIGHT & DIAMETER :	Height 287mm Diameter 66mm
› FILLED WEIGHT (with bracket) :	0.76kg
› CYLINDER COLOUR :	Red

› EXTINGUISHER :	600g ABC Powder
› PRODUCT CODE :	AEABC600S
› MEDIUM :	ABC 40 Powder
› PROPELLANT :	Nitrogen gas
› FIRE RATING :	3A 21B C
› OPERATING TEMPERATURE :	-20°C to +50°C
› AVERAGE DISCHARGE TIME :	6 seconds
› RANGE OF DISCHARGE :	2-3 metres
› HEIGHT & DIAMETER :	Height 287mm Diameter 66mm
› FILLED WEIGHT (with bracket) :	0.76kg
› CYLINDER COLOUR :	Silver

› EXTINGUISHER :	600g ABC Powder
› PRODUCT CODE :	AEABC600S
› MEDIUM :	ABC 40 Powder
› PROPELLANT :	Nitrogen gas
› FIRE RATING :	3A 21B C
› OPERATING TEMPERATURE :	-20°C to +50°C
› AVERAGE DISCHARGE TIME :	6 seconds
› RANGE OF DISCHARGE :	2-3 metres
› HEIGHT & DIAMETER :	Height 287mm Diameter 66mm
› FILLED WEIGHT (with bracket) :	0.76kg
› CYLINDER COLOUR :	Silver