

Powder

The Basic Range Powder fire extinguisher is available in 1 and 2kg ABC powder models. For use on Class A, B and C fires making them suitable for use in environments containing multiple fire risks. They are highly effective against petrol and volatile liquids which makes them ideal for vehicle protection. Both models are Kitemark certified to BS EN3 and CE marked, with the 2kg extinguisher also approved to Merchant Shipping (Marine Equipment) Regulations SI 2016/1025.

- › Colour coded header labels.
- › Nickel plated brass valves.



FULLY CERTIFIED



› EPS1Z : 1kg ABC Powder



› EPS2ZMER : 2kg ABC Powder

Product Certification and Specification



*2kg model only.

› EXTINGUISHER :	1kg ABC Powder
› PRODUCT CODE :	EPS1Z
› MEDIUM :	ABC Powder
› PROPELLANT :	Nitrogen gas
› FIRE RATING :	5A 34B C
› OPERATING TEMPERATURE :	-30°C to +60°C
› OPERATING PRESSURE :	14 bar at 20°C
› AVERAGE DISCHARGE TIME :	6 seconds
› HEIGHT & DIAMETER :	H 330mm D 85mm
› FILLED WEIGHT :	1.96kg
› PACKING SPEC (HxWxD) :	360 x 135 x 90mm

1kg ABC Powder
EPS1Z
ABC Powder
Nitrogen gas
5A 34B C
-30°C to +60°C
14 bar at 20°C
6 seconds
H 330mm D 85mm
1.96kg
360 x 135 x 90mm

2kg ABC Powder
EPS2ZMER
ABC Powder
Nitrogen gas
13A 70B C
-30°C to +60°C
14 bar at 20°C
9 seconds
H 378mm D 110mm
3.47kg
405 x 135 x 115mm